



NEOS TECHNOLOGIES

A Gooch & Housego Company

DEVICE SPECIFICATIONS

MODEL NUMBER:

23080-3-1.06-LTD

DOCUMENT NUMBER: 56A00693E

<u>PARAMETER</u>	<u>SPECIFICATION</u>
Interactive Material	TeO ₂
Acoustic Mode	Longitudinal
Operating Wavelength	1064nm
Window Configuration	AR Coated
Static Transmission	>97 %
Operating Frequency	80 MHz
Diffraction Efficiency	>70 % With Linear Polarization, Perpendicular to Acoustic Propagation. >65 % With Random Polarization.
Acoustic Aperture Size	3 mm
Rise Time	150 ns/mm Beam Diameter
Deflection Angle	20 mrad
RF Power Level	<2 Watts
Impedance	50 Ohms
VSWR	<1.2:1 @ 80 MHz
Package:	53B0624 TO2
Operating Manual: Use Latest Revision.	51A14950
Acceptance Test Procedure:	42A12053
Acceptance Test Results form:	52A11828
Recommended Drivers:	
Analog Driver System: 21080-2AS	Digital Driver System: 21080-2DS
Analog Driver Module: 21080-2AM	Digital Driver Module: 21080-2DM

For More Information, Contact: neos@neostech.com **Ph. (321) 242-7818** **Fax (321) 242-1019**