



NEOS TECHNOLOGIES

A Gooch & Housego Company

DEVICE SPECIFICATIONS

MODEL NUMBER:

32024-70-7

DOCUMENT NUMBER: 56A14307A

<u>PARAMETER</u>	<u>SPECIFICATION</u>
Interactive Material	Fused Silica
Acoustic Mode	Shear
Operating Wavelength	1064 nm
Window Configuration	AR "V" Coated
Static Transmission	>99 %
Operating Frequency	24 MHz
Insertion Loss	<10 % @ 50 Watts
Loss Modulation	>55 % @ 1064 nm
Light Polarization	Random
Acoustic Aperture Size	7X13 mm
Rise Time	175 ns/mm Beam Diameter
Deflection Angle	6.8 mrad
RF Power Level	70 Watts
Impedance	50 Ohms
VSWR	1.2:1 @ 24 MHz
Package: Water Cooled @ 0.1GPM <30°C	53B00290
Operating Manual: Use Latest Revision.	51A00400
Acceptance Test Procedure:	42A12277
Acceptance Test Results form:	52A00657
Recommended Driver:	
Digital Driver System: 39024-70DS***	
Digital Driver Module: 38024-70DM** or 39024-70DM***	
Options: ** = PK, PKPW *** = PPK, FPS, A05, R05	

For More Information, Contact: neos@neostech.com **Ph. (321) 242-7818** **Fax (321) 242-1019**