



# NEOS TECHNOLOGIES

A Gooch & Housego Company

## DEVICE SPECIFICATIONS

MODEL NUMBER:

**32024-100-4**

DOCUMENT NUMBER: 56A14308A

<u>PARAMETER</u>	<u>SPECIFICATION</u>
Interactive Material	Fused Silica
Acoustic Mode	Shear
Operating Wavelength	1064 nm
Window Configuration	AR "V" Coated
Static Transmission	>99 %
Operating Frequency	24 MHz
Insertion Loss	<10 % @ 50 Watts
Loss Modulation	>90 % @ 1064 nm
Light Polarization	Random
Acoustic Aperture Size	4X13 mm
Rise Time	175 ns/mm Beam Diameter
Deflection Angle	6.8 mrad
RF Power Level	100 Watts
Impedance	50 Ohms
VSWR	1.2:1 @ 24 MHz
Package: Water Cooled @ 0.1GPM <30°C	53B00290
Operating Manual: Use Latest Revision.	51A00400
Acceptance Test Procedure:	42A12277
Acceptance Test Results form:	52A00657
Recommended Driver:	
Digital Driver System: 39024-100DS***	
Digital Driver Module: 38024-100DM** or 39024-100DM***	
Options: ** =PK, PKPW      *** = PPK, FPS, A05, R05	

**For More Information, Contact:**      [neos@neostech.com](mailto:neos@neostech.com)      **Ph. (321) 242-7818**      **Fax (321) 242-1019**