



NEOS TECHNOLOGIES

A Gooch & Housego Company

DEVICE SPECIFICATIONS

MODEL NUMBER:

32027-70-7

DOCUMENT NUMBER: 56A14309A

<u>PARAMETER</u>	<u>SPECIFICATION</u>
Interactive Material	Fused Silica
Acoustic Mode	Shear
Operating Wavelength	1064 nm
Window Configuration	AR "V" Coated
Static Transmission	>99 %
Operating Frequency	27.12MHz
Insertion Loss	<10 % @ 50 Watts
Loss Modulation	>55 %
Light Polarization	Random
Acoustic Aperture Size	7 X 13 mm
Rise Time	175 ns / mm Beam Diameter
Deflection Angle	7.6 mrad
RF Power Level	70 Watts
Impedance	50 Ohms
VSWR	<1.2:1 @ 27.12 MHz
Package: Water Cooled @ 0.1GPM <30°C	53B00290
Operating Manual: Use Latest Revision.	51A00400
Acceptance Test Procedure:	42A12277
Acceptance Test Results form:	52A00657
Recommended Driver:	
Digital Driver System: 39027-70DS***	
Digital Driver Module: 38027-70DM** or 39027-70DM***	
Options: ** =PK, PKPW *** = PPK, FPS, A05, R05	

For More Information, Contact:

neos@neostech.com Ph. (321) 242-7818

Fax (321) 242-1019

56A14309A.doc

1 OF 1

32027-70-7

APPROVED 3/22/04 W SEALE

ECO# 58A15961