



NEOS TECHNOLOGIES

A Gooch & Housego Company

DEVICE SPECIFICATIONS

MODEL NUMBER

12080-3-TE

DOCUMENT NUMBER: 56A14293C

<u>PARAMETER</u>	<u>SPECIFICATION</u>
Interactive Material	SiO ₂
Acoustic Mode	Longitudinal
Operating Wavelength	1.06 μ m
Window Configuration	AR "V" Coated
Static Transmission	>99 %
Operating Frequency	80 MHz \pm 150 KHz
Mode spacing	300 KHz Typical
Mode Bandwidth -3dB	10 KHz approximate
Average Loss Modulation	10 % minimum with Linear Polarized Light, Perpendicular to Acoustic Propagation
Acoustic Aperture Size	3 mm
Deflection Angle	14.2 mrad
RF Power Level	<1.2 watt
Impedance	50 ohms @ Resonant Frequency
VSWR	<1.5:1 @ Resonant Frequency
Package:	53A2198
Operating Manual: Use Latest Rev.	51A02804
Acceptance Test Procedure:	42A14128
Acceptance Test Results Form:	52A02807
Recommended Driver:	11080-1ML

For More Information, Contact: neos@neostech.com Ph. (321) 242-7818 Fax (321) 242-1019